

OFFICIAL QUOTE

200KVA 575 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER






200KVA 575 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$10,972.50 CAD

Single Phase Autotransformer with a capacity of 200kVA, transforming 575 Volts to 277 Volts

SKU: MC200J1-D Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 200kVA, transforming 575 Volts to 277 Volts



OFFICIAL QUOTE

200KVA 575 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	815.6 lbs
Phases	1
kVA	200
Connection	<u>1PhA-NT-1</u>
Primary Voltage	<u>575</u>
Primary Max Current	<u>200.8A</u>
Primary Markings	<u>H0-H1</u>
Primary Terminals	<u>600MCM-2</u>
Secondary Voltage	277
Secondary Max Current	<u>416.9A</u>
Secondary Markings	<u>X0-X1</u>
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	<u>55 dB</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8S</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

200KVA 575 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM