


OFFICIAL QUOTE

150KVA 480 VOLTS TO 400 VOLTS SINGLE PHASE AUTOTRANSFORMER





150KVA 480 VOLTS TO 400 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$3,666.80 CAD

Single Phase Autotransformer with a capacity of 150kVA, transforming 480 Volts to 400 Volts

SKU: MC150H-G1

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 150kVA, transforming 480 Volts to 400 Volts



OFFICIAL QUOTE



150KVA 480 VOLTS TO 400 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 247.3 lbs |
| Phases | 1 |
| kVA | 150 |
| Connection | 1PhA-NT-1 |
| Primary Voltage | 480 |
| Primary Max Current | <u>180.4A</u> |
| Primary Markings | <u>H0-H1</u> |
| Primary Terminals | 300MCM-6 |
| Secondary Voltage | 400 |
| Secondary Max Current | 216.5A |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | 600MCM-2 |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 0.5 – 1.5% |
| Sound (db) | 45 dB |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

150KVA 480 VOLTS TO 400 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|