



## 15KVA 480 VOLTS TO 240 VOLTS THREE PHASE ENCAPSULATED AUTOTRANSFORMER



**\$2,550.00 CAD**

Three Phase Encapsulated Autotransformer with a capacity of 15kVA, transforming 480Y Volts to 240Y Volts

**SKU:** RC15H-C/EP

**Categories:** [Encapsulated Autotransformer](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Encapsulated Autotransformer with a capacity of 15kVA, transforming 480Y Volts to 240Y Volts



## PRODUCT SPECIFICATIONS

Weight	400 lbs
Phases	<a href="#">3</a>
kVA	<a href="#">15</a>
Connection	<a href="#">3PhA-NT-1</a>
Primary Voltage	<a href="#">480</a>
Primary Markings	<a href="#">H1-H2-H3</a>
Primary Terminals	<a href="#">#2-14 AWG</a>
Secondary Voltage	<a href="#">240</a>
Secondary Markings	<a href="#">X1-X2-X3</a>
Secondary Terminals	<a href="#">#2-14 AWG</a>
Primary Taps	<a href="#">N/A</a>
Conductor Material	<a href="#">Copper</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">0.5 – 1.5%</a>
Sound (db)	<a href="#">45</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-3PEP-3</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperatue Rise	<a href="#">130°C</a>
Insuation Class	<a href="#">200°C (Class N)</a>