



7.5KVA 400 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$1,914.53 CAD

Single Phase Isolation Transformer with a capacity of 7.5kVA, transforming 400 Volts to 220/440 Volts

SKU: SC7G1-L2

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 7.5kVA, transforming 400 Volts to 220/440 Volts

7.5KVA 400 VOLTS TO 220/440 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



PRODUCT SPECIFICATIONS

| | |
|----------------------------|--|
| Weight | 128 lbs |
| Phases | 1 |
| kVA | 7.5 |
| Connection | 1Ph-1coil-3T-SD |
| Primary Voltage | 400 |
| Primary Max Current | 18.75A |
| Primary Markings | H1-H2 |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 220/440 |
| Secondary Max Current | 34.09A |
| Secondary Markings | X1-X2 |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | +/- 1 x 5% |
| Conductor Material | Copper |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 5.0 – 7.0% |
| Sound (db) | 40 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-4 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 150°C |



OFFICIAL QUOTE

7.5KVA 400 VOLTS TO 220/440 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



| | |
|----------------------|--|
| Insuation Class | 150°C |
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |