



## CS250J-L

**\$193.00 CAD**

SKU: ddeac1990d88

Categories: [Control Transformers](#)

### PRODUCT SPECIFICATIONS

Weight	10 lbs
Phases	<a href="#">1</a>
VA	<a href="#">250</a>
Connection	<a href="#">1Ph-CT-SD-SD</a>
Primary Voltage	<a href="#">600</a>
Primary Max Current	<a href="#">0.42A</a>
Primary Markings	<a href="#">H1-H2</a>
Primary Terminals	<a href="#">Terminals</a>
Secondary Voltage	<a href="#">240/480</a>
Secondary Max Current	<a href="#">1.04A</a>



<b>Secondary Markings</b>	<a href="#">X1-X2-X3-X4</a>
<b>Secondary Terminals</b>	<a href="#">Terminals</a>
<b>Primary Taps</b>	<a href="#">N/A</a>
<b>Conductor Material</b>	<a href="#">Copper</a>
<b>Temperatue Rise</b>	<a href="#">80°C</a>
<b>Insuation Class</b>	<a href="#">130°C</a>
<b>BIL (Insulation) Level</b>	<a href="#">10kV</a>
<b>Efficiency</b>	<a href="#">N/A</a>
<b>Impedance</b>	<a href="#">5.0 – 7.0%</a>
<b>Sound (db)</b>	<a href="#">40</a>
<b>Enclosure Type</b>	<a href="#">Core &amp; Coil</a>
<b>Enclosure</b>	<a href="#">See Chart</a>
<b>Standards &amp; Certifications</b>	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered</a>
<b>Finish</b>	<a href="#">N/AN/A</a>