

750KVA 115 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER

$25,978.60 CAD

Three Phase Autotransformer with a capacity of 750kVA, transforming 115Y Volts to 416Y Volts

SKU: RA750A1-G
Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 750kVA, transforming 115Y Volts to 416Y Volts

PRODUCT SPECIFICATIONS

Weight	3605 lbs
Phases	3
kVA	750
Connection	3PhA-NT-1
Primary Voltage	115
Primary Max Current	3765.3A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	416
Secondary Max Current	1040.9A
Secondary Markings	H1-H2-H3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	62
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-11
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered

Country/Manufacturer	Canada/RPM