

OFFICIAL QUOTE

750KVA 240 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER





750KVA 240 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$74,836.02 CAD


Three Phase Isolation Transformer with a capacity of 750kVA, transforming 240 Volts to 415Y/240 Volts

SKU: BC750C-N2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 750kVA, transforming 240 Volts to 415Y/240 Volts



OFFICIAL QUOTE



750KVA 240 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	4795 lbs
Phases	<u>3</u>
kVA	750
Connection	3Ph-DY-5CT-SU
Primary Voltage	240
Primary Max Current	1804.22A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	415Y/240
Secondary Max Current	1043.4A
Secondary Markings	<u>H0-H1-H2-H3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	99.23% (DOE 2016/NRCan 2019)
Impedance Range	<u>5.0 - 7.0%</u>
Sound (db)	64
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-11
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE



750KVA 240 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey