





## OFFICIAL QUOTE

### 9KVA 600 VOLTS TO 440Y/254 VOLTS THREE PHASE ISOLATION TRANSFORMER



#### PRODUCT SPECIFICATIONS

|                                       |  |
|---------------------------------------|--|
| <b>Weight</b>                         | 132 lbs  |
| <b>Phases</b>                         | <a href="#">3</a>  |
| <b>kVA</b>                            | <a href="#">9</a>  |
| <b>Connection</b>                     | <a href="#">3Ph-DY-3T-SD</a>   |
| <b>Primary Voltage</b>                | <a href="#">600</a>  |
| <b>Primary Max Current</b>            | <a href="#">8.66A</a>  |
| <b>Primary Markings</b>               | <a href="#">H1-H2-H3</a>   |
| <b>Primary Terminals</b>              | <a href="#">#2-14 AWG</a>  |
| <b>Secondary Voltage</b>              | <a href="#">440Y/254</a>   |
| <b>Secondary Max Current</b>          | <a href="#">11.81A</a>   |
| <b>Secondary Markings</b>             | <a href="#">X0-X1-X2-X3</a>  |
| <b>Secondary Terminals</b>            | <a href="#">#2-14 AWG</a>  |
| <b>Primary Taps</b>                   | <a href="#">+/- 1 x 5%</a>   |
| <b>Conductor Material</b>             | <a href="#">Copper</a>   |
| <b>BIL (Insulation) Level</b>         | <a href="#">10kV</a>   |
| <b>Efficiency (@35% Load) %</b>       | <a href="#">N/A</a>  |
| <b>Impedance Range</b>                | <a href="#">5.0 – 7.0%</a>   |
| <b>Sound (db)</b>                     | <a href="#">40</a>   |
| <b>Enclosure Type</b>                 | <a href="#">NEMA 3R Indoor</a>   |
| <b>Enclosure Size</b>                 | <a href="#">E3R-4</a>  |
| <b>Finish/Colour</b>                  | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>   |
| <b>Standards &amp; Certifications</b> | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |
| <b>Temperatue Rise</b>                | <a href="#">150°C</a>  |



OFFICIAL QUOTE

9KVA 600 VOLTS TO 440Y/254 VOLTS  
THREE PHASE ISOLATION  
TRANSFORMER



|                      |  |
|----------------------|--|
| Insuation Class      | <a href="#">150°C</a>                                    |
| Country/Manufacturer | <a href="#">Canada/RPM</a>                               |
| Finish/Colour        | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a> |