

OFFICIAL QUOTE

225KVA 277 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER





225KVA 277 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$14,008.30 CAD

Single Phase Autotransformer with a capacity of 225kVA, transforming 277 Volts to 110 Volts

SKU: MC225D-A2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 225kVA, transforming 277 Volts to 110 Volts



OFFICIAL QUOTE



225KVA 277 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	1047.6 lbs
Phases	1
kVA	225
Connection	<u>1PhA-NT-1</u>
Primary Voltage	277
Primary Max Current	469A
Primary Markings	<u>H0-H1</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	110
Secondary Max Current	1180.9A
Secondary Markings	<u>X0-X1</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	<u>55 dB</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8S
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

225KVA 277 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------