

OFFICIAL QUOTE

75KVA 120 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER





75KVA 120 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER


\$6,770.70 CAD

Three Phase Autotransformer with a capacity of 75kVA, transforming 120Y Volts to 347Y Volts

SKU: RC75A-E

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 75kVA, transforming 120Y Volts to 347Y Volts



OFFICIAL QUOTE



75KVA 120 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	395 lbs
Phases	3
kVA	<u>75</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	120
Primary Max Current	360.8A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	347
Secondary Max Current	124.8A
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>2.5 - 4.5%</u>
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 120 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------