

#### **OFFICIAL QUOTE**

### 15KVA 110 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER





### 15KVA 110 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,046.13 USD

Three Phase Autotransformer with a capacity of 15kVA, transforming 110Y Volts to 600Y Volts

SKU: RC15A2-J

**Categories:** Autotransformer

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Autotransformer with a capacity of 15kVA, transforming 110Y Volts to 600Y Volts



### **OFFICIAL QUOTE**



# 15KVA 110 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER

### **PRODUCT SPECIFICATIONS**

| PRODUCT SPECIFICATIONS     |  |
|----------------------------|--|
| Weight                     | 96 lbs   |
| Phases                     | <u>3</u>   |
| kVA                        | <u>15</u>  |
| Connection                 | 3PhA-NT-1  |
| Primary Voltage            | 110  |
| Primary Max Current        | 78.7A  |
| Primary Markings           | <u>X1-X2-X3</u>  |
| Primary Terminals          | #2/0-6 AWG   |
| Secondary Voltage          | 600  |
| Secondary Max Current      | 14.4A  |
| Secondary Markings         | H1-H2-H3   |
| Secondary Terminals        | Terminal Blocks  |
| Primary Taps               | N/A  |
| Conductor Material         | Copper   |
| Insulation Class           | 220°C (Class H)  |
| BIL (Insulation) Level     | <u>10kV</u>  |
| Efficiency (@35% Load) %   | N/A  |
| Impedance Range            | <u>2.5 – 4.5%</u>  |
| Sound (db)                 | 45   |
| Enclosure Type             | NEMA 3R Indoor   |
| Enclosure Size             | <u>E3R-5</u>   |
| Finish/Colour              | Polyester Powder Coat – ANSI/ASA 61 Grey   |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



### **OFFICIAL QUOTE**

# 15KVA 110 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|