



330KVA 400 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$20,081.38 USD

Single Phase Isolation Transformer with a capacity
of 330kVA, transforming 400 Volts to 220/440
Volts

SKU: SC330G1-L2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 330kVA, transforming 400 Volts to 220/440 Volts



PRODUCT SPECIFICATIONS

| | |
|----------------------------|--|
| Weight | 1720 lbs |
| Phases | 1 |
| kVA | 330 |
| Connection | 1Ph-2coil-5t-SD |
| Primary Voltage | 400 |
| Primary Max Current | 825.0A |
| Primary Markings | H1-H2 |
| Primary Terminals | Pads |
| Secondary Voltage | 220/440 |
| Secondary Max Current | 1500.0A |
| Secondary Markings | X1-X2 |
| Secondary Terminals | Pads |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Copper |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 98.90% (DOE 2016/NRCAN 2019) |
| Impedance Range | 4.0 – 6.0% |
| Sound (db) | 55 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-9S |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperature Rise | 150°C |



OFFICIAL QUOTE

330KVA 400 VOLTS TO 220/440
VOLTS SINGLE PHASE ISOLATION
TRANSFORMER



| | |
|----------------------|--|
| Insuation Class | 150°C |
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |