

### **OFFICIAL QUOTE**

## 112KVA 200 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER





## 112KVA 200 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER

\$8,025.30 CAD

Three Phase Autotransformer with a capacity of 112.5kVA, transforming 200Y Volts to 416Y Volts

**SKU:** RC112B1-G

**Categories:** Autotransformer


### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 112.5kVA, transforming 200Y Volts to 416Y Volts







### **PRODUCT SPECIFICATIONS**

Weight	480 lbs
Phases	<u>3</u>
kVA	112.5
Connection	3PhA-NT-1
Primary Voltage	200
Primary Max Current	<u>324.8A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	416
Secondary Max Current	<u>156.1A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-7</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

# 112KVA 200 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------