



**6KVA 460 VOLTS TO 208Y/120 VOLTS
THREE PHASE ENCAPSULATED
ISOLATION TRANSFORMER**



**6KVA 460 VOLTS TO
208Y/120 VOLTS THREE
PHASE ENCAPSULATED
ISOLATION TRANSFORMER**


\$2,068.82 USD

Three Phase Encapsulated Isolation Transformer
with a capacity of 6kVA, transforming 460 Volts to
208Y/120 Volts

SKU: BC6H1-M/EP

Categories: [Encapsulated Isolation Transformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Encapsulated Isolation Transformer with a capacity of 6kVA, transforming 460 Volts to 208Y/120 Volts

6KVA 460 VOLTS TO 208Y/120 VOLTS
THREE PHASE ENCAPSULATED
ISOLATION TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	185 lbs
Phases	3
kVA	6
Connection	3Ph-DY-3T-SD
Primary Voltage	460
Primary Max Current	288.7A
Primary Markings	H1-H2-3
Primary Terminals	#2-14 AWG
Secondary Voltage	208Y/120
Secondary Max Current	16.7A
Secondary Markings	X0-X1-X2-X3
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 1 x 5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	40
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-3PEP-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Country/Manufacturer	Canada/RPM