



75VA 600 VOLTS TO 460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$7,032.19 CAD

Single Phase Isolation Transformer with a capacity of 75kVA, transforming 600 Volts to 460 Volts

SKU: SC75J-H1/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 75kVA, transforming 600 Volts to 460 Volts



PRODUCT SPECIFICATIONS

Weight	444 lbs
Phases	1
kVA	75
Connection	1Ph-2coil-5t-SD
Primary Voltage	600
Primary Max Current	125.0A
Primary Markings	H1-H2
Primary Terminals	300 MCM – 6
Secondary Voltage	460
Secondary Max Current	163.04A
Secondary Markings	X1-X2
Secondary Terminals	300 MCM – 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.50% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE
75VA 600 VOLTS TO 460 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey