



112KVA 460 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER



\$2,864.10 CAD

Three Phase Autotransformer with a capacity of 112.5kVA, transforming 460Y Volts to 380Y Volts

SKU: RA112H1-F

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 112.5kVA, transforming 460Y Volts to 380Y Volts



PRODUCT SPECIFICATIONS

Weight	123 lbs
Phases	3
kVA	112.5
Connection	3PhA-NT-1
Primary Voltage	460
Primary Max Current	141.2A
Primary Markings	H1-H2-H3
Primary Terminals	300MCM-6
Secondary Voltage	380
Secondary Max Current	170.9A
Secondary Markings	X1-X2-X3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
112KVA 460 VOLTS TO 380 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------