



150VA 480 VOLTS TO 460Y/266 VOLTS THREE PHASE ISOLATION TRANSFORMER



\$12,051.62 USD

Three Phase Isolation Transformer with a capacity of 150kVA, transforming 480 Volts to 460Y/266 Volts

SKU: BC150H-P1/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 150kVA, transforming 480 Volts to 460Y/266 Volts



PRODUCT SPECIFICATIONS

Weight	1040 lbs
Phases	3
kVA	150
Connection	3Ph-DY-5T-SD
Primary Voltage	480
Primary Max Current	180.42A
Primary Markings	H1-H2-H3
Primary Terminals	300 MCM – 6
Secondary Voltage	460Y/266
Secondary Max Current	188.27A
Secondary Markings	X0-X1-X2-X3
Secondary Terminals	300 MCM – 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.83% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

150VA 480 VOLTS TO 460Y/266
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey