


### **OFFICIAL QUOTE**

## 15KVA 230 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER





# 15KVA 230 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$1,763.80 CAD


Single Phase Autotransformer with a capacity of 15kVA, transforming 230 Volts to 440 Volts

**SKU:** MC15C1-H2

**Categories:** Autotransformer

### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Single Phase Autotransformer with a capacity of 15kVA, transforming 230 Volts to 440 Volts



## **OFFICIAL QUOTE**



# 15KVA 230 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS     |  |
|----------------------------|--|
| Weight                     | 99.8 lbs   |
| Phases                     | 1  |
| kVA                        | <u>15</u>  |
| Connection                 | <u>1PhA-NT-1</u>   |
| Primary Voltage            | 230  |
| Primary Max Current        | 37.7A  |
| Primary Markings           | <u>X0-X1</u>   |
| Primary Terminals          | #2-14 AWG  |
| Secondary Voltage          | 440  |
| Secondary Max Current      | <u>19.7A</u>   |
| Secondary Markings         | <u>H0-H1</u>   |
| Secondary Terminals        | Terminal Blocks  |
| Primary Taps               | N/A  |
| Conductor Material         | Copper   |
| Insulation Class           | 220°C (Class H)  |
| BIL (Insulation) Level     | <u>10kV</u>  |
| Efficiency (@35% Load) %   | N/A  |
| Impedance Range            | 1.5 - 3.5%   |
| Sound (db)                 | 40 dB  |
| Enclosure Type             | NEMA 1   |
| Enclosure Size             | <u>E1-2</u>  |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey   |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



## **OFFICIAL QUOTE**

# 15KVA 230 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|