


OFFICIAL QUOTE

1500KVA 600 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER





1500KVA 600 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER


\$31,793.00 CAD


Three Phase Autotransformer with a capacity of 1500kVA, transforming 600Y Volts to 416Y Volts

SKU: RA1500J-G

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 1500kVA, transforming 600Y Volts to 416Y Volts



OFFICIAL QUOTE



1500KVA 600 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	2981 lbs
Phases	<u>3</u>
kVA	1500
Connection	3PhA-NT-1
Primary Voltage	600
Primary Max Current	<u>1443.4A</u>
Primary Markings	H1-H2-H3
Primary Terminals	<u>Pads</u>
Secondary Voltage	416
Secondary Max Current	2081.8A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 - 3.0%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-10
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

1500KVA 600 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------