

#### **OFFICIAL QUOTE**

## 150VA 240 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER





# 150VA 240 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$19,339.32 CAD


Three Phase Isolation Transformer with a capacity of 150kVA, transforming 240 Volts to 380Y/220 Volts

**SKU:** BC150C-R/Z3

**Categories:** <u>Isolation Transformers</u>

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 150kVA, transforming 240 Volts to 380Y/220 Volts



### **OFFICIAL QUOTE**



## 150VA 240 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

### **PRODUCT SPECIFICATIONS**

| Weight                     | 1040 lbs                                                                             |
|----------------------------|--------------------------------------------------------------------------------------|
| Phases                     | <u>3</u>                                                                             |
| kVA                        | 150                                                                                  |
| Connection                 | 3Ph-DY-5T-SU                                                                         |
| Primary Voltage            | 240                                                                                  |
| Primary Max Current        | 360.84A                                                                              |
| Primary Markings           | X1-X2-X3                                                                             |
| Primary Terminals          | <u>Pads</u>                                                                          |
| Secondary Voltage          | 380Y/220                                                                             |
| Secondary Max Current      | 227.9A                                                                               |
| Secondary Markings         | <u>H0-H1-H2-H3</u>                                                                   |
| Secondary Terminals        | <u>Pads</u>                                                                          |
| Primary Taps               | +/- 2 x 2.5%                                                                         |
| Conductor Material         | Copper                                                                               |
| BIL (Insulation) Level     | 10kV                                                                                 |
| Efficiency (@35% Load) %   | 98.83% (DOE 2016/NRCan 2019)                                                         |
| Impedance Range            | 4.0 - 6.0%                                                                           |
| Sound (db)                 | <u>50</u>                                                                            |
| Enclosure Type             | NEMA 3R Indoor                                                                       |
| Enclosure Size             | E3R-8                                                                                |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey                                             |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise            | 150°C                                                                                |



### **OFFICIAL QUOTE**



## 150VA 240 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class      | 150°C                                    |
|----------------------|------------------------------------------|
| Country/Manufacturer | Canada/RPM                               |
| Finish/Colour        | Polyester Powder Coat - ANSI/ASA 61 Grey |