


#### **OFFICIAL QUOTE**

## 150KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER





### 150KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER

\$5,577.27 USD

Three Phase Autotransformer with a capacity of 150kVA, transforming 550Y Volts to 347Y Volts

**SKU:** RC150J2-E

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 550Y Volts to 347Y Volts



### **OFFICIAL QUOTE**



# 150KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS     |  |
|----------------------------|--|
| Weight                     | 454 lbs  |
| Phases                     | <u>3</u>   |
| kVA                        | 150  |
| Connection                 | 3PhA-NT-1  |
| Primary Voltage            | <u>550</u>   |
| Primary Max Current        | 157.5A   |
| Primary Markings           | H1-H2-H3   |
| Primary Terminals          | 300MCM-6   |
| Secondary Voltage          | 347  |
| Secondary Max Current      | 249.6A   |
| Secondary Markings         | <u>X1-X2-X3</u>  |
| Secondary Terminals        | 600MCM-2   |
| Primary Taps               | N/A  |
| Conductor Material         | Copper   |
| Insulation Class           | 220°C (Class H)  |
| BIL (Insulation) Level     | <u>10kV</u>  |
| Efficiency (@35% Load) %   | N/A  |
| Impedance Range            | 1.0 - 3.0%   |
| Sound (db)                 | <u>55</u>  |
| Enclosure Type             | NEMA 3R Indoor   |
| Enclosure Size             | <u>E3R-7</u>   |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey   |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



### **OFFICIAL QUOTE**

# 150KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|