




**150KVA 400 VOLTS TO 347 VOLTS
THREE PHASE AUTOTRANSFORMER**



150KVA 400 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER



\$2,286.00 USD

Three Phase Autotransformer with a capacity of 150kVA, transforming 400Y Volts to 347Y Volts

SKU: RC150G1-E

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 150kVA, transforming 400Y Volts to 347Y Volts



PRODUCT SPECIFICATIONS

Weight	168 lbs
Phases	3
kVA	150
Connection	3PhA-NT-1
Primary Voltage	400
Primary Max Current	216.5A
Primary Markings	H1-H2-H3
Primary Terminals	600MCM-2
Secondary Voltage	347
Secondary Max Current	249.6A
Secondary Markings	X1-X2-X3
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
150KVA 400 VOLTS TO 347 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------