


OFFICIAL QUOTE

50KVA 277 VOLTS TO 115 VOLTS SINGLE PHASE AUTOTRANSFORMER





50KVA 277 VOLTS TO 115 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$4,135.00 CAD


Single Phase Autotransformer with a capacity of 50kVA, transforming 277 Volts to 115 Volts

SKU: MC50D-A1

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 50kVA, transforming 277 Volts to 115 Volts



OFFICIAL QUOTE



50KVA 277 VOLTS TO 115 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 262.5 lbs |
| Phases | 1 |
| kVA | <u>50</u> |
| Connection | 1PhA-NT-1 |
| Primary Voltage | 120/240 |
| Primary Max Current | 104.2A |
| Primary Markings | <u>H0-H1</u> |
| Primary Terminals | #2/0-6 AWG |
| Secondary Voltage | 115 |
| Secondary Max Current | 251A |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | 600MCM-2 |
| Primary Taps | N/A |
| Conductor Material | <u>Copper</u> |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.5 – 3.5% |
| Sound (db) | 45 dB |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

50KVA 277 VOLTS TO 115 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|