

#### **OFFICIAL QUOTE**

## 2500KVA 600 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER





# 2500KVA 600 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER


\$17,807.18 USD

Three Phase Autotransformer with a capacity of 2500kVA, transforming 600Y Volts to 550Y Volts

**SKU:** RA2500J-J2

**Categories:** Autotransformer

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Autotransformer with a capacity of 2500kVA, transforming 600Y Volts to 550Y Volts



### **OFFICIAL QUOTE**





### **PRODUCT SPECIFICATIONS**

PRODUCT SPECIFICATIONS	
Weight	1420 lbs
Phases	3
kVA	2500
Connection	3PhA-NT-1
Primary Voltage	600
Primary Max Current	2405.6A
Primary Markings	H1-H2-H3
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>550</u>
Secondary Max Current	2624.3A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	<u>Aluminum</u>
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>0.5 - 1.5%</u>
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-9</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

## 2500KVA 600 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	<u>Canada/RPM</u>
----------------------	-------------------