


OFFICIAL QUOTE

225KVA 380 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER





225KVA 380 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$6,080.30 CAD


Single Phase Autotransformer with a capacity of 225kVA, transforming 380 Volts to 480 Volts

SKU: MC225F-H

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 225kVA, transforming 380 Volts to 480 Volts



OFFICIAL QUOTE

225KVA 380 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 414.5 lbs |
|----------------------------|---|
| Phases | 1 |
| kVA | 225 |
| Connection | 1PhA-NT-1 |
| Primary Voltage | 380 |
| Primary Max Current | <u>341.9A</u> |
| Primary Markings | <u>X0-X1</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 480 |
| Secondary Max Current | 270.6A |
| Secondary Markings | <u>H0-H1</u> |
| Secondary Terminals | 600MCM-2 |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.0 - 3.0% |
| Sound (db) | 45 dB |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

225KVA 380 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|