



30KVA 416 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER

\$1,861.65 USD

Three Phase Autotransformer with a capacity of 30kVA, transforming 416Y Volts to 575Y Volts

SKU: RC30G-J1

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 30kVA, transforming 416Y Volts to 575Y Volts



PRODUCT SPECIFICATIONS

Weight	61 lbs
Phases	3
kVA	30
Connection	3PhA-NT-1
Primary Voltage	416
Primary Max Current	41.6A
Primary Markings	X1-X2-X3
Primary Terminals	#2-14 AWG
Secondary Voltage	575
Secondary Max Current	30.1A
Secondary Markings	H1-H2-H3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

30KVA 416 VOLTS TO 575 VOLTS

THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------