

OFFICIAL QUOTE

2500KVA 600 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER





2500KVA 600 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER


\$32,114.10 CAD

Three Phase Autotransformer with a capacity of 2500kVA, transforming 600Y Volts to 460Y Volts

SKU: RA2500J-H1

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 2500kVA, transforming 600Y Volts to 460Y Volts



OFFICIAL QUOTE



2500KVA 600 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--------------------------------------------------------------------------------------|
| Weight | 3917 lbs |
| Phases | <u>3</u> |
| kVA | 2500 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 600 |
| Primary Max Current | 2405.6A |
| Primary Markings | <u>H1-H2-H3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 460 |
| Secondary Max Current | 3137.8A |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.0 - 3.0% |
| Sound (db) | <u>62</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-11</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

2500KVA 600 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|