

OFFICIAL QUOTE

2000KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER





2000KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER


\$35,338.20 CAD


Three Phase Autotransformer with a capacity of 2000kVA, transforming 550Y Volts to 347Y Volts

SKU: RA2000J2-E

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 2000kVA, transforming 550Y Volts to 347Y Volts



OFFICIAL QUOTE

2000KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 5135 lbs |
|----------------------------|--|
| Phases | <u>3</u> |
| kVA | 2000 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 550 |
| Primary Max Current | 2099.5A |
| Primary Markings | <u>H1-H2-H3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 347 |
| Secondary Max Current | 3327.7A |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.0 - 3.0% |
| Sound (db) | 64 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-11</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

2000KVA 550 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|