

OFFICIAL QUOTE

1500KVA 400 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER





1500KVA 400 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER


\$28,723.20 CAD

Three Phase Autotransformer with a capacity of 1500kVA, transforming 400Y Volts to 240Y Volts

SKU: RA1500G1-C

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 1500kVA, transforming 400Y Volts to 240Y Volts



OFFICIAL QUOTE



1500KVA 400 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 4046 lbs |
| Phases | <u>3</u> |
| kVA | 1500 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 400 |
| Primary Max Current | 2165.1A |
| Primary Markings | <u>H1-H2-H3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 240 |
| Secondary Max Current | 3608.4A |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.0 - 3.0% |
| Sound (db) | <u>62</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-11</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

1500KVA 400 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|