




37.5KVA 230 VOLTS TO 575 VOLTS SINGLE PHASE AUTOTRANSFORMER



\$3,391.10 CAD

Single Phase Autotransformer with a capacity of
37.5kVA, transforming 230 Volts to 575 Volts

SKU: MC37C1-J1

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 37.5kVA, transforming 230 Volts to 575 Volts



PRODUCT SPECIFICATIONS

Weight	212.6 lbs
Phases	1
kVA	37.5
Connection	1PhA-NT-1
Primary Voltage	230
Primary Max Current	94.1A
Primary Markings	X0-X1
Primary Terminals	#2/0-6 AWG
Secondary Voltage	575
Secondary Max Current	37.7A
Secondary Markings	H0-H1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

37.5KVA 230 VOLTS TO 575 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------