



## 5KVA 460 VOLTS TO 120/240 VOLTS SINGLE PHASE ENCAPSULATED ISOLATION TRANSFORMER


**\$1,714.00 CAD**

Single Phase Encapsulated Isolation Transformer  
with a capacity of 5kVA, transforming 460 Volts to  
120/240 Volts

**SKU:** SC5H1-K/EP

**Categories:** [Encapsulated Isolation Transformer](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Encapsulated Isolation Transformer with a capacity of 5kVA, transforming 460 Volts to 120/240 Volts

5KVA 460 VOLTS TO 120/240 VOLTS  
SINGLE PHASE ENCAPSULATED  
ISOLATION TRANSFORMER



## PRODUCT SPECIFICATIONS

Weight	155 lbs
Phases	<a href="#">1</a>
kVA	<a href="#">5</a>
Connection	<a href="#">1Ph-2coil-3t-SD</a>
Primary Voltage	<a href="#">460</a>
Primary Max Current	<a href="#">10.9A</a>
Primary Markings	<a href="#">H1-H2</a>
Primary Terminals	<a href="#">#2-14 AWG</a>
Secondary Voltage	<a href="#">120/240</a>
Secondary Max Current	<a href="#">41.7A</a>
Secondary Markings	<a href="#">X1-X3-X2-X4</a>
Secondary Terminals	<a href="#">#2-14 AWG</a>
Primary Taps	<a href="#">+/- 1 x 5%</a>
Conductor Material	<a href="#">Copper</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">1.5 – 3.5%</a>
Sound (db)	<a href="#">40</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-1PEP-4</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>