

OFFICIAL QUOTE

37.5KVA 550 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER





37.5KVA 550 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$1,410.70 CAD

Single Phase Autotransformer with a capacity of 37.5kVA, transforming 550 Volts to 480 Volts

SKU: MC37J2-H

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 37.5kVA, transforming 550 Volts to 480 Volts



OFFICIAL QUOTE



37.5KVA 550 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 86.1 lbs |
| Phases | 1 |
| kVA | <u>37.5</u> |
| Connection | <u>1PhA-NT-1</u> |
| Primary Voltage | <u>550</u> |
| Primary Max Current | 39.4A |
| Primary Markings | <u>H0-H1</u> |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 480 |
| Secondary Max Current | 45.1A |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 0.5 – 1.5% |
| Sound (db) | 40 dB |
| Enclosure Type | NEMA 1 |
| Enclosure Size | <u>E1-2</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

37.5KVA 550 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|