



225KVA 230 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$5,120.60 CAD

Single Phase Autotransformer with a capacity of
225kVA, transforming 230 Volts to 277 Volts

SKU: MC225C1-D

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 225kVA, transforming 230 Volts to 277 Volts



PRODUCT SPECIFICATIONS

Weight	352.5 lbs
Phases	1
kVA	225
Connection	1PhA-NT-1
Primary Voltage	230
Primary Max Current	564.8A
Primary Markings	X0-X1
Primary Terminals	Pads
Secondary Voltage	277
Secondary Max Current	469A
Secondary Markings	H0-H1
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
225KVA 230 VOLTS TO 277 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------