

#### **OFFICIAL QUOTE**

## 225KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER





# 225KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER


\$13,759.20 CAD


Three Phase Autotransformer with a capacity of 225kVA, transforming 550Y Volts to 277Y Volts

SKU: RC225J2-D

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 550Y Volts to 277Y Volts



### **OFFICIAL QUOTE**

## 225KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER



### **PRODUCT SPECIFICATIONS**

Wainba	1016 lbs
Weight	1016 lbs
Phases	3
kVA	225
Connection	3PhA-NT-1
Primary Voltage	<u>550</u>
Primary Max Current	236.2A
Primary Markings	H1-H2-H3
Primary Terminals	600MCM-2
Secondary Voltage	277
Secondary Max Current	469A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

## 225KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------