



37.5KVA 550 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$1,336.18 USD

Single Phase Autotransformer with a capacity of
37.5kVA, transforming 550 Volts to 440 Volts

SKU: MC37J2-H2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 37.5kVA, transforming 550 Volts to 440 Volts



PRODUCT SPECIFICATIONS

Weight	105.6 lbs
Phases	1
kVA	37.5
Connection	1PhA-NT-1
Primary Voltage	550
Primary Max Current	39.4A
Primary Markings	H0-H1
Primary Terminals	#2-14 AWG
Secondary Voltage	440
Secondary Max Current	49.2A
Secondary Markings	X0-X1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

37.5KVA 550 VOLTS TO 440 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------