



450KVA 120 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER

\$35,235.20 CAD

Three Phase Autotransformer with a capacity of 450kVA, transforming 120Y Volts to 460Y Volts

SKU: RC450A-H1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 450kVA, transforming 120Y Volts to 460Y Volts



PRODUCT SPECIFICATIONS

Weight	2737 lbs
Phases	3
kVA	450
Connection	3PhA-NT-1
Primary Voltage	120
Primary Max Current	2165.1A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	460
Secondary Max Current	564.8A
Secondary Markings	H1-H2-H3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-10
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

450KVA 120 VOLTS TO 460 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------