



2500KVA 277 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER


\$33,235.20 CAD

Three Phase Autotransformer with a capacity of 2500kVA, transforming 277Y Volts to 240Y Volts

SKU: RA2500D-C

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 2500kVA, transforming 277Y Volts to 240Y Volts



PRODUCT SPECIFICATIONS

Weight	2062 lbs
Phases	3
kVA	2500
Connection	3PhA-NT-1
Primary Voltage	277
Primary Max Current	5210.7A
Primary Markings	H1-H2-H3
Primary Terminals	Pads
Secondary Voltage	240
Secondary Max Current	6014.1A
Secondary Markings	X1-X2-X3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-10
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

2500KVA 277 VOLTS TO 240 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------