



## 15KVA 416 VOLTS TO 240/480 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

**\$2,472.93 CAD**

Single Phase Isolation Transformer with a capacity of 15kVA, transforming 416 Volts to 240/480 Volts

**SKU:** SA15G-L/Z3

**Categories:** [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 15kVA, transforming 416 Volts to 240/480 Volts

15KVA 416 VOLTS TO 240/480 VOLTS  
SINGLE PHASE ISOLATION  
TRANSFORMER



## PRODUCT SPECIFICATIONS

|                            |  |
|----------------------------|--|
| Weight                     | 143 lbs  |
| Phases                     | <a href="#">1</a>  |
| kVA                        | <a href="#">15</a>   |
| Connection                 | <a href="#">1Ph-2coil-5t-SD</a>  |
| Primary Voltage            | <a href="#">416</a>  |
| Primary Max Current        | <a href="#">36.06A</a>   |
| Primary Markings           | <a href="#">H1-H2</a>  |
| Primary Terminals          | <a href="#">#2-14 AWG</a>  |
| Secondary Voltage          | <a href="#">240/480</a>  |
| Secondary Max Current      | <a href="#">62.5A</a>  |
| Secondary Markings         | <a href="#">X1-X2</a>  |
| Secondary Terminals        | <a href="#">#2-14 AWG</a>  |
| Primary Taps               | <a href="#">+/- 2 x 2.5%</a>   |
| Conductor Material         | <a href="#">Aluminum</a>   |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency (@35% Load) %   | <a href="#">97.70% (DOE 2016/NRCan 2019)</a>   |
| Impedance Range            | <a href="#">4.0 – 6.0%</a>   |
| Sound (db)                 | <a href="#">45</a>   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>   |
| Enclosure Size             | <a href="#">E3R-4</a>  |
| Finish/Colour              | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>   |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |
| Temperatue Rise            | <a href="#">150°C</a>  |



OFFICIAL QUOTE

15KVA 416 VOLTS TO 240/480 VOLTS  
SINGLE PHASE ISOLATION  
TRANSFORMER



|                      |  |
|----------------------|--|
| Insuation Class      | <a href="#">150°C</a>                                    |
| Country/Manufacturer | <a href="#">Canada/RPM</a>                               |
| Finish/Colour        | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a> |