



50KVA 550 VOLTS TO 416 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$2,319.60 CAD

Single Phase Autotransformer with a capacity of 50kVA, transforming 550 Volts to 416 Volts

SKU: MC50J2-G

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 50kVA, transforming 550 Volts to 416 Volts



PRODUCT SPECIFICATIONS

Weight	140.8 lbs
Phases	1
kVA	50
Connection	1PhA-NT-1
Primary Voltage	550
Primary Max Current	52.5A
Primary Markings	H0-H1
Primary Terminals	#2-14 AWG
Secondary Voltage	416
Secondary Max Current	69.4A
Secondary Markings	X0-X1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

50KVA 550 VOLTS TO 416 VOLTS

SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------