

#### **OFFICIAL QUOTE**

## 150KVA 600 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





### 150KVA 600 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER


\$10,269.64 USD


Three Phase Autotransformer with a capacity of 150kVA, transforming 600Y Volts to 115Y Volts

**SKU:** RC150J-A1

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 600Y Volts to 115Y Volts



### **OFFICIAL QUOTE**





### **PRODUCT SPECIFICATIONS**

| Weight                     | 1118 lbs   |
|----------------------------|--|
| Phases                     | <u>3</u>   |
| kVA                        | <u>150</u>   |
| Connection                 | 3PhA-NT-1  |
| Primary Voltage            | 600  |
| Primary Max Current        | 144.3A   |
| Primary Markings           | <u>H1-H2-H3</u>  |
| Primary Terminals          | 300MCM-6   |
| Secondary Voltage          | 115  |
| Secondary Max Current      | 753.1A   |
| Secondary Markings         | <u>X1-X2-X3</u>  |
| Secondary Terminals        | <u>Pads</u>  |
| Primary Taps               | N/A  |
| Conductor Material         | Copper   |
| Insulation Class           | 220°C (Class H)  |
| BIL (Insulation) Level     | <u>10kV</u>  |
| Efficiency (@35% Load) %   | N/A  |
| Impedance Range            | 2.5 - 4.5%   |
| Sound (db)                 | <u>55</u>  |
| Enclosure Type             | NEMA 3R Indoor   |
| Enclosure Size             | <u>E3R-8</u>   |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey   |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



### **OFFICIAL QUOTE**

# 150KVA 600 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | <u>Canada/RPM</u> |
|----------------------|-------------------|
|----------------------|-------------------|