


OFFICIAL QUOTE

150KVA 240 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





150KVA 240 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

\$9,625.00 CAD


Three Phase Autotransformer with a capacity of 150kVA, transforming 240Y Volts to 115Y Volts

SKU: RC150C-A1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 240Y Volts to 115Y Volts



OFFICIAL QUOTE



150KVA 240 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|---|
| Weight | 674 lbs |
| Phases | <u>3</u> |
| kVA | 150 |
| Connection | <u>3PhA-NT-1</u> |
| Primary Voltage | 240 |
| Primary Max Current | 360.8A |
| Primary Markings | H1-H2-H3 |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 115 |
| Secondary Max Current | 753.1A |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.5 - 3.5% |
| Sound (db) | <u>55</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-7</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

150KVA 240 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | <u>Canada/RPM</u> |
|----------------------|-------------------|
|----------------------|-------------------|