

OFFICIAL QUOTE

750KVA 480 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





750KVA 480 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$10,588.23 USD


Three Phase Autotransformer with a capacity of 750kVA, transforming 480Y Volts to 575Y Volts

SKU: RC750H-J1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 750kVA, transforming 480Y Volts to 575Y Volts



OFFICIAL QUOTE





PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	1146 lbs
Phases	<u>3</u>
kVA	<u>750</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	480
Primary Max Current	902.1A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>575</u>
Secondary Max Current	753.1A
Secondary Markings	H1-H2-H3
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>0.5 – 1.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

750KVA 480 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------