

OFFICIAL QUOTE

750KVA 380 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





750KVA 380 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$23,606.30 CAD

Three Phase Autotransformer with a capacity of 750kVA, transforming 380Y Volts to 575Y Volts

SKU: RC750F-J1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 750kVA, transforming 380Y Volts to 575Y Volts



OFFICIAL QUOTE

750KVA 380 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	2382 lbs
Phases	<u>3</u>
kVA	750
Connection	3PhA-NT-1
Primary Voltage	380
Primary Max Current	<u>1139.5A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>575</u>
Secondary Max Current	753.1A
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 - 3.0%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-9</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

750KVA 380 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------