

OFFICIAL QUOTE

600KVA 575 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER





600KVA 575 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER


\$13,923.00 CAD


Three Phase Autotransformer with a capacity of 600kVA, transforming 575Y Volts to 460Y Volts

SKU: RC600J1-H1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 600kVA, transforming 575Y Volts to 460Y Volts



OFFICIAL QUOTE



600KVA 575 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 1104 lbs |
| Phases | <u>3</u> |
| kVA | 600 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | <u>575</u> |
| Primary Max Current | 602.5A |
| Primary Markings | <u>H1-H2-H3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 460 |
| Secondary Max Current | <u>753.1A</u> |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 0.5 - 1.5% |
| Sound (db) | <u>55</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-8</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

600KVA 575 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|