




OFFICIAL QUOTE

600KVA 480 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER



600KVA 480 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER



\$7,935.00 CAD

Three Phase Autotransformer with a capacity of 600kVA, transforming 480Y Volts to 440Y Volts

SKU: RC600H-H2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 600kVA, transforming 480Y Volts to 440Y Volts



OFFICIAL QUOTE

600KVA 480 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	404 lbs
Phases	3
kVA	600
Connection	3PhA-NT-1
Primary Voltage	480
Primary Max Current	721.7A
Primary Markings	H1-H2-H3
Primary Terminals	Pads
Secondary Voltage	440
Secondary Max Current	787.3A
Secondary Markings	X1-X2-X3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

600KVA 480 VOLTS TO 440 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)