

#### **OFFICIAL QUOTE**

## 100KVA 600 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





# 100KVA 600 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$7,299.67 USD

Single Phase Isolation Transformer with a capacity of 100kVA, transforming 600 Volts to 110/220 Volts

SKU: SC100J-K2/Z3

**Categories:** <u>Isolation Transformers</u>

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Single Phase Isolation Transformer with a capacity of 100kVA, transforming 600 Volts to 110/220 Volts



## **OFFICIAL QUOTE**



# 100KVA 600 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

## **PRODUCT SPECIFICATIONS**

PRODUCT SPECIFICATIONS	
Weight	711 lbs
Phases	1
kVA	100
Connection	1Ph-2coil-5t-SD
Primary Voltage	600
Primary Max Current	166.67A
Primary Markings	H1-H2
Primary Terminals	<u>300 MCM – 6</u>
Secondary Voltage	110/220
Secondary Max Current	909.09A
Secondary Markings	<u>X1-X2</u>
Secondary Terminals	<u>300 MCM – 6</u>
Primary Taps	+/- 2 x 2.5%
Conductor Material	<u>Copper</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	98.60% (DOE 2016/NRCan 2019)
Impedance Range	4.0 - 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8S</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



## **OFFICIAL QUOTE**



# 100KVA 600 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey