



200KVA 440 VOLTS TO 120 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$14,938.50 CAD

Single Phase Autotransformer with a capacity of 200kVA, transforming 440 Volts to 120 Volts

SKU: MC200H2-A

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 200kVA, transforming 440 Volts to 120 Volts



PRODUCT SPECIFICATIONS

Weight	1113.7 lbs
Phases	1
kVA	200
Connection	1PhA-NT-1
Primary Voltage	440
Primary Max Current	262.4A
Primary Markings	H0-H1
Primary Terminals	600MCM-2
Secondary Voltage	120
Secondary Max Current	962.3A
Secondary Markings	X0-X1
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	55 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8S
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

200KVA 440 VOLTS TO 120 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------