

OFFICIAL QUOTE

37.5KVA 240 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





37.5KVA 240 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$4,386.48 CAD

Single Phase Isolation Transformer with a capacity of 37.5kVA, transforming 240 Volts to 380 Volts

SKU: SC37C-F/Z3 Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 37.5kVA, transforming 240 Volts to 380 Volts



OFFICIAL QUOTE

TRANSFORMER

37.5KVA 240 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION



PRODUCT SPECIFICATIONS

Weight	272 lbs
Phases	1
kVA	37.5
Connection	1Ph-2coil-5T-SU
Primary Voltage	240
Primary Max Current	<u>156.25A</u>
Primary Markings	<u>X1-X2</u>
Primary Terminals	<u>300 MCM – 6</u>
Secondary Voltage	380
Secondary Max Current	<u>98.68A</u>
Secondary Markings	<u>H1-H2</u>
Secondary Terminals	<u>300 MCM – 6</u>
Primary Taps	<u>+/-2 x 2.5%</u>
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	98.20% (DOE 2016/NRCan 2019)
Impedance Range	<u>4.0 - 6.0%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	<u>150°C</u>

The quote is valid 30 days from 15 June 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



OFFICIAL QUOTE

37.5KVA 240 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



Insuation Class	<u>150°C</u>
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey