



150VA 550 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$18,595.50 CAD

Three Phase Isolation Transformer with a capacity of 150kVA, transforming 550 Volts to 220Y/127 Volts

SKU: BC150J2-S2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 150kVA, transforming 550 Volts to 220Y/127 Volts



PRODUCT SPECIFICATIONS

Weight	1040 lbs
Phases	3
kVA	150
Connection	3Ph-DY-5T-SD
Primary Voltage	550
Primary Max Current	157.46A
Primary Markings	H1-H2-H3
Primary Terminals	300 MCM – 6
Secondary Voltage	220Y/127
Secondary Max Current	393.65A
Secondary Markings	X0-X1-X2-X3
Secondary Terminals	300 MCM – 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.83% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

150VA 550 VOLTS TO 220Y/127
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey