

OFFICIAL QUOTE

100KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER





100KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$6,348.00 CAD

Single Phase Autotransformer with a capacity of 100kVA, transforming 208 Volts to 440 Volts

SKU: MC100B-H2

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 100kVA, transforming 208 Volts to 440 Volts



OFFICIAL QUOTE



100KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	437.5 lbs
Phases	1
kVA	100
Connection	<u>1PhA-NT-1</u>
Primary Voltage	208
Primary Max Current	277.6A
Primary Markings	<u>X0-X1</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	440
Secondary Max Current	131.2A
Secondary Markings	<u>H0-H1</u>
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	<u>55 dB</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-7</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

100KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------